Artmark LED

LEDing the Way

100

Parking and Street Lighting

USES AND APPLICATIONS
PARKING AREA AND STREET LIGHTING

100 Watts

LIGHT STATS	
Lumens	9000 Lm
Watts	100W
LM/Watt	90Lm/W
CRI	70 minimum
Life Hours	50,000 Hrs.
Amp. Draw	0.83A@120V/0.43A@230V/0.36A@277V
Voltage	110~277V
K Temp.	4000K, 5000K, 5700K
NEMA	IP 65
Certification	UL
Warranty	5 Years

SPECIFICATIONS:

Ref. No.	Description	Dimensions	Weight
ARTSL100W40-*-YY-XX-**	100W LED 120~277V 4000K	25" x 15" x 7.1"	18.7 Lbs.
ARTSL100W50-*-YY-XX-**	100W LED 120~277V 5000K	25" x 15" x 7.1"	18.7 Lbs.
ARTSL100W57-*-YY-XX-**	100W LED 120~277V 5700K	25" x 15" x 7.1"	18.7 Lbs.

OPTIONS:

* =	YY=	XX= (Color)	**=
T2: TYPE II Distribution	**D:** Dimmable	**GR:** Grey	**LC:** with Photocell Receptacle
T3: TYPE III Distribution	**ND:** Non-dimmable	**BR:** Bronze	**SLC:** No Photocell
T5: Type V Distribution		**BL:** Black	

UL LISTED E468343

5 YEAR WARRANTY