# Artmark LED

LEDing the Way

120

# Parking and Street Lighting

## USES AND APPLICATIONS
PARKING AREA AND STREET LIGHTING

**120 Watts**

| LIGHT STATS | |
|---|---|
| **Lumens** | 10800 Lm |
| **Watts** | 120W |
| **LM/Watt** | 94Lm/W |
| **CRI** | 70 minimum |
| **Life Hours** | 50,000 Hrs. |
| **Amp. Draw** | 1.0A@120V/.52A@230V/.43A@277V |
| **Voltage** | 110~277V |
| **K Temp.** | 4000K, 5000K, 5700K |
| **NEMA** | IP 65 |
| **Certification** | UL |
| **Warranty** | 5 Years |
| **# of LEDs** | 20 LED (4 bars x 5) |

**SPECIFICATIONS:**

| Ref. No. | Descripción | Dimensiones | Peso |
|---|---|---|---|
| ARTSL120W40-*-YY-XX-** | 120W LED 120~277V 4000K | 27" x 15" x 7.1" | 21.2 Lbs. |
| ARTSL120W50-*-YY-XX-** | 120W LED 120~277V 5000K | 27" x 15" x 7.1" | 21.2 Lbs. |
| ARTSL120W57-*-YY-XX-** | 120W LED 120~277V 5700K | 27" x 15" x 7.1" | 21.2 Lbs. |

**OPTIONS:**

| * = | YY= | XX= (Color) | **= |
|---|---|---|---|
| **T2:** TYPE II Distribution | **D:** Dimmable | **GR:** Grey | **LC:** with Photocell Receptacle |
| **T3:** TYPE III Distribution | **ND:** Non-dimmable | **BR:** Bronze | **SLC:** No Photocell |
| **T5:** Type V Distribution | | **BL:** Black | |

UL LISTED E468343

5 YEAR WARRANTY