# Artmark LED

LEDing the Way

160

# Parking and Parking Lighting

## USES AND APPLICATIONS
PARKING AREA AND STREET LIGHTING

**160 Watts**

| LIGHT STATS | |
|---|---|
| **Lumens** | 14400 Lm |
| **Watts** | 160W |
| **LM/Watt** | 94Lm/W |
| **CRI** | 70 minimum |
| **Life Hours** | 50,000 Hrs. |
| **Amp. Draw** | 1.34A@120V/.7A@230V/.58A@277V |
| **Voltage** | 110~277V |
| **K Temp.** | 4000K, 5000K, 5700K |
| **Operating** | -35ºC ~ +50ºC |
| **NEMA** | IP 65 |
| **Certification** | UL E468343 |
| **Warranty** | 5 Years |
| **# of LEDs** | 25 LED (5 bars x 5) |

**SPECIFICATIONS:**

| Ref. No. | Descripción | Dimensiones | Peso |
|---|---|---|---|
| ARTSL160W40-*-YY-XX-** | 160W LED 120~277V 4000K | 30” x 15” x 7.1” | 23.8 Lbs. |
| ARTSL160W50-*-YY-XX-** | 160W LED 120~277V 5000K | 30” x 15” x 7.1” | 23.8 Lbs. |
| ARTSL160W57-*-YY-XX-** | 160W LED 120~277V 5700K | 30” x 15” x 7.1” | 23.8 Lbs. |

DLC QPL LISTED

UL LISTED E468343

5 YEAR WARRANTY

**OPTIONS:**

| * = | YY= | XX= (Color) | **= |
|---|---|---|---|
| **T2:** TYPE II Distribution | **D:** Dimmable | **GR:** Grey | **LC:** with Photocell Receptacle |
| **T3:** TYPE III Distribution | **ND:** Non-dimmable | **BR:** Bronze | **SLC:** No Photocell |
| **T5:** Type V Distribution | | **BL:** Black | |