Artmark LED

LEDing the Way

Parking and Street Lighting

60

USES AND APPLICATIONS
PARKING AREA AND STREET LIGHTING

60 Watts

LIGHT STATS	
Lumens	5400 Lm
Watts	60W
LM/Watt	94Lm/W
CRI	70 minimum
Life Hours	50,000 Hrs.
Amp. Draw	0.5A@120V/0.26A@230V/0.22A@277 V
Voltage	110~277V
K Temp.	4000K, 5000K, 5700K
NEMA	IP 65
Certification	UL E468343
Warranty	5 Years

SPECIFICATIONS:

Ref. No.	Description	Dimensions	WEIGHT
ARTSL60W40-*-YY-XX-**	60W LED 120~277V 4000K	23" x 15" x 7.1"	15.9 Lbs.
ARTSL60W50-*-YY-XX-**	60W LED 120~277V 5000K	23" x 15" x 7.1"	15.9 Lbs.
ARTSL60W57-*-YY-XX-**	60W LED 120~277V 5700K	23" x 15" x 7.1"	15.9 Lbs.

DLC QPL LISTED

UL LISTED E468343

5 YEAR WARRANTY

OPTIONS:

* =	YY=	XX= (Color)	**=
T2: TYPE II Distribution	**D:** Dimmable	**GR:** Grey	**LC:** With Photocell Receptacle
T3: TYPE III Distribution	**ND:** Non Dimmable	**BR:** Bronze	**SLC:** No Photocell
T5: Type V Distribution		**BL:** Black	