



APC Fittings

# Straight Liquid Tight Connectors

## Zinc Die Cast





### Applications:

Straight liquid tight connector are used for joining flexible LT conduit to a junction box at 0° angle (straight).

Available in sizes: 3/8", 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3" & 4".

APC straight liquid tight connectors can be installed where UL listed product is required.



ARTMARK Cat. No.	Size	Standard Carton 	Weight/ Carton (Lbs)	A (mm)	B (mm)	C (mm)	A (")	B (")	C (")
ARTLTSCONN038ZDC	3/8"	200	34.0	33.0	32.6	12.7	1.30	1.28	0.50
ARTLTSCONN050ZDC	1/2"	200	28.0	33.5	32.0	12.5	1.32	1.26	0.49
ARTLTSCONN075ZDC	3/4"	100	22.0	40.3	33.0	12.5	1.59	1.30	0.49
ARTLTSCONN100ZDC	1"	50	18.0	45.4	40.5	16.8	1.79	1.59	0.66
ARTLTSCONN125ZDC	1-1/4"	50	29.0	57.9	44.5	16.6	2.28	1.75	0.65
ARTLTSCONN150ZDC	1-1/2"	20	14.5	63.4	44.5	17.0	2.50	1.75	0.67
ARTLTSCONN200ZDC	2"	20	18.0	76.8	45.5	16.5	3.02	1.79	0.65
ARTLTSCONN250ZDC	2-1/2"	1	2.0	95.2	68.0	24.0	3.75	2.68	0.94
ARTLTSCONN300ZDC	3"	1	4.0	110.5	66.0	24.6	4.35	2.60	0.97
ARTLTSCONN400ZDC	4"	1	5.0	133.0	77.0	26.0	5.24	3.03	1.02

11315 NW 36 TER Miami, FL 33178 Tel: (305) 715-9800 Fax: (305) 715-9988

<http://www.artmark.com>

Liquid Tight Straight Liquid Tight Connector