



APC Fittings

# BX Flexible Metallic Tubing

## Applications:

For industrial and commercial use in circuit protection and internal wiring in dry areas. It is also suitable for the protection of electrical cables machinery, tools and equipment that do not require listed product and use them on not exposed to the weather areas.


### Available in Sizes:

3/8", 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3" & 4" on coils and

## Construction:

Internal flexible metal pipe corrosion resistant galvanized with a system interlock / square squarelock This tube is impact resistant and of high flexibility.



ARTMARK Cat. No.	Size	Standard Package (Ft) 	Weight / Package Std. (Lbs)	Internal Diameter (mm)		External Diameter (mm)		Curving radius Minimum (mm)
				Min.	Max.	Min.	Max.	
ARTSFLXC038	3/8"	100	11	9.3	9.7	14.1	14.5	50
ARTSFLXC050	1/2"	100	17	16.4	16.9	21.6	22.0	76
ARTSFLXC075	3/4"	100	20	20.7	21.2	26.5	27.0	100
ARTSFLXC100	1"	100	25	26.0	26.5	32.5	33.0	125
ARTSFLXC125	1-1/4"	50	22	33.0	33.6	38.4	39.0	158
ARTSFLXC150	1-1/2"	50	24	37.6	38.2	46.4	47.0	180
ARTSFLXC200	2"	50	30	51.5	52.1	59.3	60.0	250
ARTSFLXC250	2-1/2"	25	23	63.5	64.5	74.0	75.0	320
ARTSFLXC300	3"	25	30	77.5	78.5	88.0	89.0	380
ARTSFLXC400	4"	25	39	103.5	104.8	113.0	114.5	500

11315 NW 36 TER Miami, FL 33178 Tel: (305) 715-9800 Fax: (305) 715-9988

<http://www.artmark.com>

B  
X  
  
S  
t  
e  
e  
l  
  
F  
l  
e  
x  
i  
b  
l  
e  
  
C  
o  
n  
d  
u  
i  
t